SSC Series Salt Chlorinator

VARIOUS MODELS FOR DIFFERENT POOL SIZES

For residential and semi-commercial pools



Product Features

- 1. Three models to choose: 15, 25, 45g/hr
- 2. With or without built-in pump timer
- 3. Self cleaning reverse polarity
- 4. Quality titanium cells
- 5. With or without built-in lighting transformer
- 6. Maximum working pressure: 250kPa/36psi/2.5bar

Emaux
water technology











Characteristics

Salt chlorination is a method of sanitizing swimming pools with chlorine generated by electrolysis. The electrolysis is achieved by passing the saltwater solution through a weak electric charge in an electrolytic cell, which converts sodium chloride (salt) in the water into chlorine gas. The gas is dissolved in the water and becomes sodium hypochlorite (liquid chlorine).


Safe and environmentally friendly, salt water technology brings you:

- Relaxation: Your pool is automatically disinfected
- Safety: Significant reduction in the need to store and handle chlorine
- Health and well-being: Saltwater does not irritate the eyes and dries out skin



Technical Information

Code 220V/50Hz	Model	Description	Salt Level (ppm)	Cell Output (gram/h)	Fiberglass Pool (L)	Concrete Pool (L)	Pool Light Voltage	Input Voltage /Freq	IP Rating	Weight (kg)
88380601 88380602 88380603	SSC15-E SSC25-E SSC50-E	Standard Version	4000	15 25 45	50,000 75,000 120,000	45,000 70,000 110,000	N/A	240V 50/60Hz	IPX4	6.5 7.4 9.7
88380401 88380402 88380403	SSC15-T SSC25-T SSC50-T	With Time Clock	4000	15 25 45	50,000 75,000 120,000	45,000 70,000 110,000	N/A	240V 50/60Hz	IPX4	6.6 7.5 9.8
88380201 88380202	SSC15-TLT SSC25-TLT	With Time Clock & Pool Light Transformer	4000	15 25	50,000 75,000	45,000 70,000	12V AC	240V 50/60Hz	IPX4	8.4 8.8



EMAUX WATER TECHNOLOGY CO., LTD

ADDRESS: Flat A-D, 20/F., Kai Bo 22, 22 Wing Kin Road,

Kwai Chung, Hong Kong PHONE +852 2832 9880 www.emauxgroup.com

Pool & Spa Equipment

Available from: